

Series 80 Mighty Mouse Technical Reference Complete Product Specification



DESCRIPTION	REQUIREMENT	PROCEDURE		
ELECTRICAL				
Contact resistance	SAE AS39029 Table V	EIA-364-06 IEC 60512-2-1 Test current in amperes. Voltage drop in millivolts. Silver-coated copper wire, +25°C.		
	Wire Size		Test Current	Max Voltage Drop
	12		23	42
	14		17	40
	16		13	49
	20		7.5	55
	22		5	73
	24		3	45
Low level contact resistance	Wire Size	Max. Milliohms	EIA-364-23 100 milliamperes maximum and 20 millivolts maximum open circuit voltage	
	16	5		
	20	9		
	22	15		
	24	20		
	26	31		
Insulation resistance	5000 megohms minimum	EIA-364-21 IEC-60512-3-1 500 volts DC ± 50 volts. Test between adjacent contacts and contacts to shell.		
	Dielectric withstanding voltage, sea level	No breakdown or flashover #23 contacts 500 volts #20HD contacts 750 volts #16 contacts 1800 volts #12 contacts 1800 volts	EIA-364-20 IEC-60512-4-1 AC rms 60 Hz. One minute dwell. Unmated or mated	
Dielectric withstanding voltage, 70,000 feet altitude	No breakdown or flashover #23 contacts 100 volts #20HD contacts 150 volts #16 contacts 1000 volts #12 contacts 1000 volts	EIA-364-20 IEC-60512-4-1 AC rms 60 Hz. One minute dwell. mated condition		
Current carrying capacity	Contact Size	Max Current	EIA-364-70 Method 1 IEC-60512-5 Test 9b	
	12	23		
	16	13		
	20	7.5		
	23	5		

Dimensions in inches (millimeters) and are subject to change without notice.

DESCRIPTION	REQUIREMENT	PROCEDURE																							
Shell-to-shell conductivity, Initial	<p>The maximum voltage drop across a mated pair shall not exceed the values shown.</p> <table border="1"> <thead> <tr> <th>Series</th> <th>Voltage Drop</th> </tr> </thead> <tbody> <tr><td>800</td><td>10</td></tr> <tr><td>801</td><td>10</td></tr> <tr><td>802</td><td>10</td></tr> <tr><td>803</td><td>100</td></tr> <tr><td>804</td><td>2</td></tr> <tr><td>805</td><td>2</td></tr> </tbody> </table>	Series	Voltage Drop	800	10	801	10	802	10	803	100	804	2	805	2	<p>EIA-364-83 IEC-60512-2-6 Electroless nickel plated connectors.</p>									
Series	Voltage Drop																								
800	10																								
801	10																								
802	10																								
803	100																								
804	2																								
805	2																								
Shell-to-shell conductivity, after conditioning (48 hours salt spray)	<p>The maximum voltage drop across a mated pair shall not exceed the values shown.</p> <table border="1"> <thead> <tr> <th>Series</th> <th>Voltage Drop</th> </tr> </thead> <tbody> <tr><td>800</td><td>20</td></tr> <tr><td>801</td><td>20</td></tr> <tr><td>802</td><td>20</td></tr> <tr><td>803</td><td>200</td></tr> <tr><td>804</td><td>4</td></tr> <tr><td>805</td><td>4</td></tr> </tbody> </table>	Series	Voltage Drop	800	20	801	20	802	20	803	200	804	4	805	4	<p>EIA-364-83 IEC-60512-2-6 Electroless nickel plated connectors.</p>									
Series	Voltage Drop																								
800	20																								
801	20																								
802	20																								
803	200																								
804	4																								
805	4																								
Shielding effectiveness, low frequency (100MHz-1000 MHz)	<table border="1"> <thead> <tr> <th rowspan="3">Frequency</th> <th colspan="2">dB Min. Attenuation</th> </tr> <tr> <th>Series 800, 801, 802, 804, 805</th> <th>Series 803</th> </tr> </thead> <tbody> <tr><td>100 MHz</td><td>75</td><td>60</td></tr> <tr><td>200 MHz</td><td>70</td><td>55</td></tr> <tr><td>300 MHz</td><td>65</td><td>55</td></tr> <tr><td>400 MHz</td><td>63</td><td>50</td></tr> <tr><td>800 MHz</td><td>58</td><td>45</td></tr> <tr><td>1000 MHz</td><td>55</td><td>40</td></tr> </tbody> </table>	Frequency	dB Min. Attenuation		Series 800, 801, 802, 804, 805	Series 803	100 MHz	75	60	200 MHz	70	55	300 MHz	65	55	400 MHz	63	50	800 MHz	58	45	1000 MHz	55	40	<p>MIL-DTL-38999 para. 4.5.28.1 Electroless nickel plated connectors</p>
Frequency	dB Min. Attenuation																								
	Series 800, 801, 802, 804, 805		Series 803																						
	100 MHz	75	60																						
200 MHz	70	55																							
300 MHz	65	55																							
400 MHz	63	50																							
800 MHz	58	45																							
1000 MHz	55	40																							
Shielding effectiveness, high frequency (1Ghz-10GHz)	<table border="1"> <thead> <tr> <th rowspan="3">Frequency</th> <th colspan="2">dB Min. Attenuation</th> </tr> <tr> <th>Series 800, 801, 802, 804</th> <th>Series 805</th> </tr> </thead> <tbody> <tr><td>1 GHz</td><td>55</td><td>85</td></tr> <tr><td>3 GHz</td><td>50</td><td>69</td></tr> <tr><td>5 GHz</td><td>45</td><td>66</td></tr> <tr><td>19 GHz</td><td>40</td><td>65</td></tr> </tbody> </table>	Frequency	dB Min. Attenuation		Series 800, 801, 802, 804	Series 805	1 GHz	55	85	3 GHz	50	69	5 GHz	45	66	19 GHz	40	65	<p>EIA-364-66 IEC-60512-23-3 Electroless nickel plated connectors</p>						
Frequency	dB Min. Attenuation																								
	Series 800, 801, 802, 804		Series 805																						
	1 GHz	55	85																						
3 GHz	50	69																							
5 GHz	45	66																							
19 GHz	40	65																							

Dimensions in inches (millimeters) and are subject to change without notice.

Series 80 Mighty Mouse Technical Reference Complete Product Specification



DESCRIPTION	REQUIREMENT	PROCEDURE
MECHANICAL		
Vibration, sine	No discontinuity of greater than 1 microsecond, no cracking, breaking or loosening of parts, plug shall not become disengaged from receptacle. Connectors shall meet electrical requirements after vibration test.	MIL-STD-202 Method 204, test Condition G 30 g's, 3 axes, 4 hours per axis
Vibration, random	No discontinuity of greater than 1 microsecond, no cracking, breaking or loosening of parts, plug shall not become disengaged from receptacle. Connectors shall meet electrical requirements after vibration test.	EIA-364-28 Test Condition V Letter I IEC-60512-6-4 100 milliamp test current 50- 2,000 Hz 37.80 g rms
Gunfire vibration	No discontinuity of greater than 1 microsecond, no cracking, breaking or loosening of parts, plug shall not become disengaged from receptacle. Connectors shall meet electrical requirements after vibration test.	MIL-STD-810F Method 519.5
Mechanical shock	No discontinuity of greater than 1 microsecond, no cracking, breaking or loosening of parts, plug shall not become disengaged from receptacle. Connectors shall meet electrical requirements after shock test.	EIA-364-27 Condition D IEC-60512-6-3 3 shocks X 3 axes X 2 directions = 18 shocks 2941 m/s ² (300 g's), 3 ms, half-sine
Mechanical durability, at ambient temperature	No deterioration which will adversely affect the connector after 2000 cycles of mating and unmating. Connectors shall meet contact resistance, insulation resistance, shell-to-shell resistance, DWV, and mating and unmating force.	EIA-364-09 IEC-60512-5 Test 9a
Solderability, PC tail contacts	95% solder coverage. Smooth, bright and even finish.	EIA-364-52 Category 3 IEC-60512-12-1 IEC-68-2-20 Test Ta, method 1 8 hours steam aging prior to test 245° C, 4-5 sec. dwell 10X magnification
Resistance To Soldering Heat	No damage to connector. Connectors shall meet insulation resistance and waterproof sealing requirements.	EIA-364-56 IEC-60512-12-5 Test 12e 260° C, 10 seconds (PC tail)

Dimensions in inches (millimeters) and are subject to change without notice.

Series 80 Mighty Mouse Technical Reference Complete Product Specification

B

DESCRIPTION	REQUIREMENT	PROCEDURE																													
Impact	No impairment of function. Connector shall meet contact resistance, insulation resistance and waterproof sealing.	EIA-364-42 IEC-60512-5 test 7b 1 meter 8 drops																													
Contact retention	<table border="1"> <thead> <tr> <th>Contact Size</th> <th>Min. Pounds</th> <th>Min. Newtons</th> </tr> </thead> <tbody> <tr> <td>23</td> <td>6</td> <td>27</td> </tr> <tr> <td>20</td> <td>15</td> <td>67</td> </tr> <tr> <td>20HD</td> <td>9</td> <td>40</td> </tr> <tr> <td>16</td> <td>25</td> <td>111</td> </tr> <tr> <td>12</td> <td>25</td> <td>111</td> </tr> </tbody> </table>	Contact Size	Min. Pounds	Min. Newtons	23	6	27	20	15	67	20HD	9	40	16	25	111	12	25	111	EIA-364-29											
Contact Size	Min. Pounds	Min. Newtons																													
23	6	27																													
20	15	67																													
20HD	9	40																													
16	25	111																													
12	25	111																													
Contact separation force	<table border="1"> <thead> <tr> <th>Contact Size</th> <th>Min. Ounces</th> <th>Min. Newtons</th> </tr> </thead> <tbody> <tr> <td>23</td> <td>0.5</td> <td>0.14</td> </tr> <tr> <td>20</td> <td>0.7</td> <td>0.19</td> </tr> <tr> <td>16</td> <td>2.0</td> <td>0.56</td> </tr> <tr> <td>12</td> <td>3.0</td> <td>0.83</td> </tr> </tbody> </table>	Contact Size	Min. Ounces	Min. Newtons	23	0.5	0.14	20	0.7	0.19	16	2.0	0.56	12	3.0	0.83	SAE AS39029														
Contact Size	Min. Ounces	Min. Newtons																													
23	0.5	0.14																													
20	0.7	0.19																													
16	2.0	0.56																													
12	3.0	0.83																													
Coupling torque	<p>Threaded coupling connector coupling torque shall not exceed the following requirements.</p> <table border="1"> <thead> <tr> <th colspan="2">Shell Size</th> <th rowspan="2">Inch Pound</th> </tr> <tr> <th>Series 800, 801</th> <th>Series 805</th> </tr> </thead> <tbody> <tr> <td>5, 6, 7</td> <td>8, 9</td> <td>8</td> </tr> <tr> <td>8,9</td> <td>10, 11</td> <td>9</td> </tr> <tr> <td>10</td> <td>12</td> <td>12</td> </tr> <tr> <td>12, 13</td> <td>15</td> <td>16</td> </tr> <tr> <td>14, 15,</td> <td>18</td> <td>28</td> </tr> <tr> <td>16, 17</td> <td>19</td> <td>24</td> </tr> <tr> <td>21</td> <td></td> <td>32</td> </tr> <tr> <td></td> <td>23</td> <td>36</td> </tr> </tbody> </table>	Shell Size		Inch Pound	Series 800, 801	Series 805	5, 6, 7	8, 9	8	8,9	10, 11	9	10	12	12	12, 13	15	16	14, 15,	18	28	16, 17	19	24	21		32		23	36	
Shell Size		Inch Pound																													
Series 800, 801	Series 805																														
5, 6, 7	8, 9	8																													
8,9	10, 11	9																													
10	12	12																													
12, 13	15	16																													
14, 15,	18	28																													
16, 17	19	24																													
21		32																													
	23	36																													
Unmating force (Series 804)	<p>Series 804 quick-disconnect connectors</p> <table border="1"> <thead> <tr> <th>Contact Arrangement</th> <th>Inch Pound</th> </tr> </thead> <tbody> <tr> <td>5-3</td> <td>10.6</td> </tr> <tr> <td>6-4</td> <td>10.8</td> </tr> <tr> <td>6-7</td> <td>11.4</td> </tr> <tr> <td>7-10</td> <td>12.0</td> </tr> <tr> <td>8-13</td> <td>12.6</td> </tr> <tr> <td>9-19</td> <td>13.8</td> </tr> <tr> <td>10-26</td> <td>15.2</td> </tr> <tr> <td>12-37</td> <td>17.4</td> </tr> <tr> <td>14-55</td> <td>21.0</td> </tr> </tbody> </table>	Contact Arrangement	Inch Pound	5-3	10.6	6-4	10.8	6-7	11.4	7-10	12.0	8-13	12.6	9-19	13.8	10-26	15.2	12-37	17.4	14-55	21.0										
Contact Arrangement	Inch Pound																														
5-3	10.6																														
6-4	10.8																														
6-7	11.4																														
7-10	12.0																														
8-13	12.6																														
9-19	13.8																														
10-26	15.2																														
12-37	17.4																														
14-55	21.0																														

Dimensions in inches (millimeters) and are subject to change without notice.

Series 80 Mighty Mouse Technical Reference Complete Product Specification



DESCRIPTION	REQUIREMENT	PROCEDURE																																															
Insert retention	<p>Unmated connectors shall retain their inserts in their proper location in the shell and there shall be no evidence of cracking, breaking, separation from the shell, or loosening of parts.</p> <table border="1"> <thead> <tr> <th colspan="3">Shell Size</th> <th rowspan="2">Min. Force in Pounds</th> </tr> <tr> <th>Ser. 800, 803, 804</th> <th>Ser. 801</th> <th>Ser. 805</th> </tr> </thead> <tbody> <tr><td>5</td><td>5</td><td></td><td>25</td></tr> <tr><td>6</td><td>6</td><td>8</td><td>25</td></tr> <tr><td>7</td><td>7</td><td>9</td><td>25</td></tr> <tr><td>8</td><td>8</td><td>10</td><td>25</td></tr> <tr><td>9</td><td>9</td><td>11</td><td>25</td></tr> <tr><td>10</td><td>10</td><td>12</td><td>25</td></tr> <tr><td>12</td><td>13</td><td>15</td><td>25</td></tr> <tr><td>14</td><td>16</td><td>18</td><td>40</td></tr> <tr><td>15</td><td>17</td><td>19</td><td>50</td></tr> <tr><td></td><td>21</td><td>23</td><td>80</td></tr> </tbody> </table>	Shell Size			Min. Force in Pounds	Ser. 800, 803, 804	Ser. 801	Ser. 805	5	5		25	6	6	8	25	7	7	9	25	8	8	10	25	9	9	11	25	10	10	12	25	12	13	15	25	14	16	18	40	15	17	19	50		21	23	80	EIA-365-35
Shell Size			Min. Force in Pounds																																														
Ser. 800, 803, 804	Ser. 801	Ser. 805																																															
5	5		25																																														
6	6	8	25																																														
7	7	9	25																																														
8	8	10	25																																														
9	9	11	25																																														
10	10	12	25																																														
12	13	15	25																																														
14	16	18	40																																														
15	17	19	50																																														
	21	23	80																																														
Residual magnetism	2 μ maximum.	EIA-364-54																																															
ENVIRONMENTAL																																																	
Operating temperature	-65° to +150°C																																																
Water immersion, mated	No evidence of water penetration into mated connectors. ≥ 100 M Ω insulation resistance.	MIL-STD-810F Method 512.4 1 meter immersion 1 hour																																															
Water immersion, open face panel mount receptacles with non-removable printed circuit board or solder cup contacts	Connectors with waterblock potting process (Glenair Modification Code 518 required). 1 X 10 ⁻⁴ cc/second maximum helium leak rate at 1 atmosphere pressure differential following thermal shock conditioning.	EIA-365-02 3 cycles thermal shock -57°C to +71°C 75 min. dwell 5 minute transfer rate																																															
Humidity, cyclic (damp heat, cyclic) (moisture resistance)	No deterioration which will adversely affect the connector. 100 megohms minimum insulation resistance during the final cycle. Following the recovery period, connectors shall meet contact resistance, shell-to-shell resistance and DWV requirements.	EIA-364-31 Condition B Method III IEC-60512-11-12 80-98% RH 10 cycles (10 days) +25° C to +65° C Step 7b vibration deleted. 24 hour recovery period.																																															

Dimensions in inches (millimeters) and are subject to change without notice.



Series 80 Mighty Mouse Technical Reference Complete Product Specification

B

DESCRIPTION	REQUIREMENT	PROCEDURE
21 day humidity (damp heat, long term)	No deterioration which will adversely affect the connector. Following the drying period, connectors shall meet 100 megohms minimum, contact resistance, shell-to-shell resistance, DWV, mating and unmating requirements.	EIA-364-31 Condition C Method II IEC-60512-11-3 Severity C 90-95% RH 40° C Apply 100 volts DC during test. 4 hours drying time at ambient temperature prior to final measurements.
Thermal shock	No mechanical damage or loosening of parts. Following thermal shock, connector shall meet contact resistance, DWV, insulation resistance and shell-to-shell resistance requirements.	EIA-364-32 Test Condition IV IEC-60512-11-4 5 cycles consisting of -65° C 30 minutes, +25° C 5 minutes max., +150° C 30 minutes, +25° C 5 minutes max.
Corrosion (salt mist)	No exposure of base metal. Connectors shall meet DWV and contact resistance requirements following the test.	EIA-364-26 IEC 60512-11-6 5% salt solution 35° C Unmated connectors Code C: 48 hours Code M: 48hours Code MT: 500 hours Code NF: 500 hours Code ZN: 500 hours Code ZNU: 500 hours Code UCR: 500 hours
Sand and dust	Mated connectors shall withstand the effects of blowing sand and dust	MIL-STD-810F, Method 510.4
Fungus	Connector materials shall be fungus inert.	MIL-STD-810F, Method 508.5
Fluid immersion	No visible damage from immersion in various fuels and oils. Connector shall meet coupling torque and dielectric withstanding voltage requirements.	EIA-364-10 Unmated connectors
Altitude immersion	No evidence of moisture on connector interface or contacts. Connector shall meet dielectric withstanding voltage.	EIA-364-03 Wired crimp connectors with supplemental potting. Printed circuit board and solder cup connectors with standard factory-installed potting.
Outgassing	The entire connector assembly shall be capable of meeting a maximum Total Mass Loss (TML) of 1% and a Total Collected Volatile Material Loss (TCVML) of 0.1% following additional processing for outgassing control.	ASTM-E595

Dimensions in inches (millimeters) and are subject to change without notice.